



Version: March 2022.  
This issue replace all previous

## UNMOULD HYDROCHROMA EXTRA WHITE PAINT FOR INTERNAL CEILINGS

Ultra-white ceiling color for interior use. It has great resistance to moisture fungi. It withstands dry rubbing and covers all surfaces with two hands. It is recommended mainly for bathrooms, kitchens and in general in areas that mean the growth of fungi and mold.

### Dilution



First coat  
15% water

Second coat  
5-10% water

### Coverage



4 - 6m<sup>2</sup>/Lt  
on properly  
prepared surfaces

### Drying



1 - 2 hours  
depending on  
the conditions

### Application tools



Brush, Roller,  
Spray gun

### Shades



White



Water based  
product



Packaging from  
recycled plastic

### Recommended undercoats



Life dur  
water



Step primer



### Packaging



It is delivered in  
containers of:

750ml

3Lt

9Lt



### Tool cleaning instructions

Keep the tools "wet" in the container during work. Drain the product thoroughly from the tools and clean them immediately with warm water and soap. If the product dries out, clean only with strong detergents. Do not empty washing liquids into the water table.



## UNMOULD HYDROCHROMA

### EXTRA WHITE PAINT FOR INTERNAL CEILINGS



#### Technical characteristics

Specific gravity	1,65-1,67	gr/lt (23°C)	ISO EN2811-01-2011
Viscosity	9500-11000	mPas (23°C)	ISO EN 2555-1999
pH	8-9	(23°C)	ISO EN 976-1996
Solids content by weight	66-68	%	ISO EN 3251-2008
Solid content by volume	40-42	%	ISO EN 3233-1998



#### Application instructions

To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc. For new or porous surfaces apply first the recommended undercoat of product (Step primer, Life dur water). Stir well the product and apply on 2 coats.



#### Application conditions

Do not apply at temperatures below **6°C** and above **40°C** and at relative humidity above **80%**. Adverse conditions in the application can alter the final properties of product.



#### Storage

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.



#### Waste management

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.



#### VOC

#### Volatile Organic Compounds

EU limit value for this product (category A/a "Interior matt paints for walls and ceilings "type WB) 30 g/l (2010). This product contains maximum **27 g/l VOC**.



#### Hygiene & safety instructions

- Keep away from children
- Avoid contact with skin and eyes
- In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice
- If swallowed, seek medical advice immediately
- The work area should be well ventilated
- When applying recommended to wear gloves and mask protection

**SAVVAS CHALIAMPALIAS & CO**  
INDUSTRIAL AREA OF THESSALONIKI, 57 022 SINDOS, GREECE  
TEL. +30 2310 79 79 72



[www.chromodomi.gr](http://www.chromodomi.gr)



For more information,  
consult the MSDS.

**Poisons Information Centre  
(Greece):**  
**+30 210 7793 777**