



chromodomi
paint & insulation

Emulsion paints

Technical data sheet

Version: January 2022.
This issue replace all previous

YDROCHROMA ULTRA

EXTRA WHITE PAINT FOR INTERNAL CEILINGS

Ydrochroma with excellent whiteness and high coverage for painting interior surfaces (walls, ceilings). It is very easy to apply, dries and repaints quickly. Suitable for surfaces where resistance to washing and staining is not required.

Dilution



First coat
15% water

Second coat
5-10% water

Coverage



5 - 7m²/Lt
on properly
prepared surfaces

Drying



1 - 2 hours
depending on
the conditions

Application tools



Brush, Roller,
Spray gun

Shades



White



Packaging



It is delivered in
containers of:

3Lt

9Lt



Tool cleaning instructions

Keep the tools "wet" in the container during work. Drain the product thoroughly from the tools and clean them immediately with warm water and soap. If the product dries out, clean only with strong detergents. Do not empty washing liquids into the water table.



BS 8493:
High reflection of light.
Reduction consumption
electricity consumption



Water based
product



Packaging from
recycled plastic

Recommended undercoats



Life dur
water



Step primer



chromodomi
paint & insulation

Emulsion paints

Technical data sheet

YDROCHROMA ULTRA

EXTRA WHITE PAINT FOR INTERNAL CEILINGS



Technical characteristics

Specific gravity	1,72	gr/lit (23°C)	ISO EN2811-01-2011
Viscosity	7400-8800	mPas (23°C)	ISO EN 2555-1999
pH	8-9	(23°C)	ISO EN 976-1996
Solids content by weight	66-68	%	ISO EN 3251-2008
Solid content by volume	38-40	%	ISO EN 3233-1998



Application instructions

To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc. For new or porous surfaces apply first the recommended undercoat of product (Step primer, Life dur water). Stir well the product and apply on **2 coats**.



Application conditions

Do not apply at temperatures below **6°C** and above **40°C** and at relative humidity above **80%**. Adverse conditions in the application can alter the final properties of product.



Storage

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.



Waste management

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.



VOC Volatile Organic Compounds

EU limit value for this product (Category A/c "Coatings for exterior walls of mineral substrate", Type WB) is 30 g/l (2010). This product contains maximum **27 g/l VOC**.



Hygiene & safety instructions

- Keep away from children
- Avoid contact with skin and eyes
- In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice
- If swallowed, seek medical advice immediately
- The work area should be well ventilated
- When applying recommended to wear gloves and mask protection

For more information,
consult the MSDS.

**Poisons Information Centre
(Greece):**
+30 210 7793 777

SAVVAS CHALIAMPALIAS & CO
INDUSTRIAL AREA OF THESSALONIKI, 57 022 SINDOS, GREECE
TEL. +30 2310 79 79 72



www.chromodomi.gr



chromodomi.gr