



### Technical data sheet

Version: May 2022  
This issue replaces all previous.

# LIFE TEX

## HIGH QUALITY ACRYLIC QUARTZ PAINT

High quality textured acrylic quartz paint for exterior use. It has great flexibility and excellent resistance to weather conditions and dirt. It is waterproof and covers perfectly capillaries and microcracks up to 2mm. Ideal for costal areas.

### Dilution



First coat  
15% water  
  
Second coat  
5-10% water

### Coverage



8 - 10m<sup>2</sup>/Lt  
per coat  
on properly  
prepared surfaces

### Drying



1 - 2 hours  
depending on  
the conditions

### Application tools



Brush, Roller, Spray gun

### Shades



White and 3 bases of our  
colouring system



Packaging from  
recycled plastic



Water based  
product



Product that has bases,  
can be coloured



### Packaging



It is delivered in  
containers of:

750ml

3Lt

10Lt



### Tool cleaning instructions

During working keep tools "liquid" in the container. Drain well the product off the tools and back in the container and clean immediately with White Spirit. If the product dries, clean the tools only with strong detergents. Do not empty washings into the groundwater.

### Recommended undercoats



Life dur  
water



Life dur



### Technical data sheet



## LIFE TEX

### HIGH QUALITY ACRYLIC QUARTZ PAINT



#### Technical characteristics

pH	8-9	(23°C)	ISO EN 976-1996
Solid content by weight	66-68	%	ISO EN 3251-2008



#### Application instructions

To ensure proper adhesion of the product, the surface to be painted must be cleaned of dust, grease, oil, peeling old paint, rust, remaining mold or moisture. For new or porous surfaces, first apply the corresponding recommended primer. Apply the product in **2 layers** (after mixing well), which should be **1 - 2 hours** apart.



#### Application conditions

Avoid application at temperatures below 6°C and above 40°C and when relative humidity is greater than 80%. Adverse conditions during application can alter the product's final properties.



#### Storage

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.

### VOC Volatile Organic Compounds

Product category A/c «Coatings for exterior walls of mineral substrate» type Y, of 2004/42/EC. Maximum limit VOC value of category: 40gr/t (2010). Maximum VOC concentration of ready to use product: **37gr/t**. Product in compliance after 2020 (Phase II).



#### Hygiene & safety instructions

- Keep away from children
- Avoid contact with skin and eyes
- In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice
- If swallowed, seek medical advice immediately
- The work area should be well ventilated
- When applying recommended to wear gloves and mask protection



#### Waste management

For leftovers of product special management is required, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

**SAVVAS CHALIAMPALIAS & CO**  
INDUSTRIAL AREA OF THESSALONIKI, 57 022 SINDOS, GREECE  
TEL. +30 2310 79 79 72



[www.chromodomi.gr](http://www.chromodomi.gr)



chromodomi.gr

For more information, consult the MSDS.

**Poisons Information Centre (Greece):**  
**+30 210 7793 777**