



Version: May 2022.
This issue replace all previous

STEP LATEX

TOP QUALITY EMULSION MASONRY PAINT

Top quality emulsion paint for indoor use. It offers great opacity and whiteness. It gives a velvety surface and spreads perfectly. Easy to work with roller, brush or gun on a cleaned surface. It has very high resistance to frequent washing. Product certified according to **EN-13300 Class 1**. Does not contain ammonia. Product certified according to **EN 71-3**. High whiteness product with certified visible light diffusion according to **BS 8493:2008** to save energy by reducing the use of lighting lamps. Certified according to **Eurofins France** and classified in the upper **class A +**, from the strictest global system for the evaluation of indoor emissions with reduced limitation in peptic organic compounds (LOW VOC) contributing to good indoor air quality.

Dilution



First coat
15% water

Second coat
5-10% water

Coverage



14 - 20m²/Lt
on properly
prepared surfaces

Drying



1 - 2 hours
depending on
the conditions

Application tools



Brush, Roller,
Spray gun

Shades



White, 10 basic shades
and 4 bases (W, P, D, TR)
of coloring system



Packaging



It is delivered in
containers of:

750ml

3Lt

10Lt



Tool cleaning instructions

Keep the tools "wet" in the container during work. Drain the product thoroughly from the tools and clean them immediately with warm water and soap. If the product dries out, clean only with strong detergents. Do not empty washing liquids into the water table.



A+ Indoor Air
Quality



EN71-3:
Certified product,
ideal for dyeing
children's clothes



EN-13300:
Product with durability
to frequent washing



BS 8493:
High reflection of light.
Reduction consumption
electricity consumption



Product tha has bases,
can be coloured



Water based
product



Packaging from
recycled plastic



STEP LATEX

TOP QUALITY EMULSION MASONRY PAINT



Technical characteristics

Specific gravity	1,57-1,59	gr/lt (23°C)	ISO EN2811-01-2011
Viscosity	7500-8000	mPas (23°C)	ISO EN 2555-1999
pH	8-9	(23°C)	ISO EN 976-1996
Solids content by weight	64-66	%	ISO EN 3251-2008
Solid content by volume	40-42	%	ISO EN 3233-1998



Application instructions

To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc. For new or porous surfaces apply first the recommended undercoat of product (Step primer, Life dur water, Step plaster). Stir well the product and apply on **2 coats**.



Application conditions

Do not apply at temperatures below **6°C** and above **40°C** and at relative humidity above **80%**. Adverse conditions in the application can alter the final properties of product.



Storage

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.



Waste management

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

VOC Volatile Organic Compounds

EU limit value for this product (category A/a "Interior matt paints for walls and ceilings "type WB) 30 g/l (2010). This product contains maximum **27 g/l VOC**.



Hygiene & safety instructions

- Keep away from children
- Avoid contact with skin and eyes
- In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice
- If swallowed, seek medical advice immediately
- The work area should be well ventilated
- When applying recommended to wear gloves and mask protection

For more information, consult the MSDS.

Poisons Information Centre (Greece):
+30 210 7793 777

SAVVAS CHALIAMPALIAS & CO
INDUSTRIAL AREA OF THESSALONIKI, 57 022 SINDOS, GREECE
TEL. +30 2310 79 79 72



www.chromodomi.gr



chromodomi.gr