



Version: May 2022.
This issue replace all previous.

COVER ACRYL HIGH QUALITY ACRYLIC CEMENT PAINT

High quality acrylic cement paint. It contains 100% acrylic emulsion that makes the surface resistant to any kind of exposure. Suitable for use on concrete, brick, plasterboard, etc. It has got great resistance to alkali of the concrete. **Certified product according to EN 71-3. Exceed Greek (EU) standard's specifications high quality emulsion paint according to the measurements of EL.OT 788.**

Dilution



First coat:
15% water.

Second coat:
5-10% water

Coverage



8-12m² / Lt
per coat
on properly
prepared surfaces

Drying



1 - 2 hours
depending on
the conditions

Application tools



Brush, Roller,
Spray gun

Shades



White, 6 basic shades: light Gray,
dark Gray, Red oxide, Black, Green, Blue
and 3 bases of
coloring system



Packaging



It is delivered in
containers of:

750ml

3Lt

9Lt/10Lt



Tool cleaning instructions

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with warm water and soap. If product dries, clean only with strong detergents. Do not empty washings into the ground-water.

Technical data sheet



Certified according
to standard
EN ELOT 788



EN71-3:
Certified product,
ideal for dyeing
children's toys



Product tha has bases,
can be coloured



Product has
basic shades



Water based
product



Packaging from
recycled plastic

Recommended undercoats



Life dur
water



Life dur



COVER ACRYL

HIGH QUALITY ACRYLIC CEMENT PAINT



Technical characteristics

Specific gravity	1,62-1,64	gr/lit (23°C)	ISO EN2811-01-2011
Viscosity	7500-8000	mPas (23°C)	ISO EN 2555-1999
pH	8-9	(23°C)	ISO EN 976-1996
Solids content by weight	67-69	%	ISO EN 3251-2008
Solid content by volume	41-43	%	ISO EN 3233-1998



Application instructions

To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc. For new or porous surfaces apply first the recommended undercoat of product (Step primer, Life dur water, Step plaster). Stir well the product and apply on **2 coats**.



Application conditions

Do not apply at temperatures below **6°C** and above **40°C** and at relative humidity above **80%**. Adverse conditions in the application can alter the final properties of product.



Storage

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.



Waste management

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

Technical data sheet



VOC Volatile Organic Compounds

Product category A/c (WB) «Coatings for exterior walls of mineral substrate» of 2004/42/EC. Maximum limit VOC value of category: 40gr/Lt. Maximum VOC concentration of ready to use product: **37gr/Lt**. Product in compliance after 2010 (Phase II).



Hygiene & safety instructions

- Keep away from children
- Avoid contact with skin and eyes
- In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice
- If swallowed, seek medical advice immediately
- The work area should be well ventilated
- When applying recommended to wear gloves and mask protection

For more information, consult the MSDS.

Poisons Information Centre
(Greece):
+30 210 7793 777

SAVVAS CHALIAMPALIAS & CO
INDUSTRIAL AREA OF THESSALONIKI, 57 022 SINDOS, GREECE
TEL. +30 2310 79 79 72



www.chromodomi.gr



chromodomi.gr