



**chromodomi**  
paint & insulation

Acrylic paints for external use

## Technical data sheet

Version: May 2022.  
This issue replace all previous.

# LIFE RELIEF

## ACRYLIC TEXTURED COATING

LIFE RELIEF is an acrylic relief coating with unique properties of durability and beauty. Its composition makes it a material suitable for painting exterior surfaces with long-term protection from harsh weather conditions, atmospheric pollution and ultraviolet radiation. By using special rollers, it can create a wide variety of decorative designs, while at the same time it can cover the small imperfections of the surface it is applied to.

### Dilution



First coat  
5% water

Second coat  
without dilution

### Coverage



1-1,5m<sup>2</sup>/kg per coat  
on properly  
prepared surfaces

### Drying



1 - 2 hours  
depending on  
the conditions

### Application tools



Brush, Roller

### Shades



White



Packaging from  
recycled plastic



Water based  
product



### Packaging



5kg



15kg

It is delivered in  
containers of:



### Tool cleaning instructions

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with warm water and soap. If product dries, clean only with strong detergents. Do not empty washings into the ground-water.

### Recommended undercoats



Life dur  
water



Life dur



## LIFE RELIEF

### ACRYLIC TEXTURED COATING



#### Technical characteristics

Specific gravity	1,76-1,78	gr/lt (23°C)	ISO EN2811-01-2011
Viscosity	60000-70000	mPas (23°C)	ISO EN 2555-1999
pH	8-9	(23°C)	ISO EN 976-1996
Solids content by weight	83-85	%	ISO EN 3251-2008
Solid content by volume	46-48	%	ISO EN 3233-1998



#### Application instructions

To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc. For new or porous surfaces apply first the recommended undercoat of the product (Life dur, Life dur water). Stir well the product and apply in 2 coats with the special RELIEF roll.



#### Application conditions

Do not apply at temperatures below **6°C** and above **40°C** and at relative humidity above **80%**. Adverse conditions in the application can alter the final properties of product.



#### Storage

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.



#### Waste management

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

#### Technical data sheet



#### VOC Volatile Organic Compounds

Product category A/c (WB) «Coatings for exterior walls of mineral substrate» of 2004/42/EC. Maximum limit VOC value of category: 40gr/Lt. Maximum VOC concentration of ready to use product: **37gr/Lt**. Product in compliance after 2010 (Phase II).



#### Hygiene & safety instructions

- Keep away from children
- Avoid contact with skin and eyes
- In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice
- If swallowed, seek medical advice immediately
- The work area should be well ventilated
- When applying recommended to wear gloves and mask protection

**SAVVAS CHALIAMPALIAS & CO**  
INDUSTRIAL AREA OF THESSALONIKI, 57 022 SINDOS, GREECE  
TEL. +30 2310 79 79 72



[www.chromodomi.gr](http://www.chromodomi.gr)



For more information,  
consult the MSDS.

**Poisons Information Centre  
(Greece):**  
**+30 210 7793 777**