

## **BEELAC**

WATER BASED BEEHIVE PAINT

( Version: October 2017 . This issue replace all previous )



### PRODUCT DESCRIPTION

Top quality 100% acrylic water based beehive paint. It is friendly to the colony, environment and the user. Provide excellent glossy surface and resistance to yellowing, while at the same time it is scentless at the application because his very low content in volatile organic compounds (VOC). It applies to any kind of old and new beehives.

### GENERAL CHARACTERISTICS

<b>COVERAGE</b>	12 - 15m <sup>2</sup> /Lt on properly prepared surfaces
<b>DILUTION</b>	If it necessary dilute with water
<b>DRYING</b>	1 - 2 hours depending on the conditions
<b>SHADES</b>	White, Poppy red, Light blue, Dark Blue, Light green, Dark green, Light Yellow, Dark Yellow, Petrol
<b>RECOMMENDED UNDERCOATS</b>	Velatura water

### APPLICATION INSTRUCTIONS

- To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc.
- Apply on surface the recommended undercoat of product
- Stir well the product and apply on surface
- The product has all the mechanical strength after 20-30 days

### APPLICATION CONDITIONS

Do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. Adverse conditions in the application can alter the final properties of product.

## APPLICATION TOOLS

### Brush, Roller, Spray gun

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with warm water and soap. If product dries, clean only with strong detergents. Do not empty washings into the groundwater.

## STORAGE

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.

## PACKAGING

It is delivered in plastic containers of **750ml, 2.5Lt**

## VOC CLASSIFICATION ( VOLATILE ORGANIC COMPOUNDS )

EU limit value for this product (Category A/d "Interior/exterior trim and cladding paints for wood, metal or plastic", Type WB) is 130 g/l (2010). This product contains maximum 127g/l VOC.

## WASTE MANAGEMENT

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

## HYGIENE & SAFETY INSTRUCTIONS

Keep away from children • Avoid contact with skin and eyes • In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice • If swallowed, seek medical advice immediately • The work area should be well ventilated • When applying recommended to wear gloves and mask protection

**For more information, consult the MSDS.**

