



Motor lac

Fast Drying Synthetic Enamel Paint



Suitable for machinery, heavy vehicles and metal constructions

- ✓ Fast drying
- ✓ High resistance
- ✓ Excellent quality
- ✓ Long lasting gloss

Excellent durability

Motor lac

Fast Drying Synthetic Enamel Paint

GENERAL CHARACTERISTICS

Fast drying, excellent quality synthetic enamel paint. It has excellent durability, long lasting gloss, withstands in hits, and has high resistance in the most adverse weather conditions. Suitable for all metal surfaces such as machinery, heavy vehicles and metal constructions

APPLICATION

Stir well before use. Do not apply at temperatures below 6°C or above 40°C or at relative humidity above 80%. It is applied on a well cleaned and primed surface on 1-2 coats with brush, roller or airless gun. It is diluted with Nitro Thinner or White Spirit at a ratio 1-5%

VOC (VOLATILE ORGANIC COMPOUNDS)

Product Category B/d (SB) 'Topcoat-All types' of the EU legislation 2004/42/EU. Maximum limit VOC value of category: 420gr/lt. Maximum VOC concentration of ready to use product 419gr/lt. Product in compliance after 2007.



Coverage:
10-15m²/Lt



Dilution: 1-5%
Nitro Thinner
or White Spirit



Drying:
20-40 min



Packaging:
750ml & 2.5Lt



Shades:
White & 23 RAL shades
and 3 bases for the coloring system

