



Tile Paint



No priming

> High water resistance

- Strong adhesion
- Excellent surface finish





Tile Paint

GENERAL CHARACTERISTICS

Special paint for tiling in the bathroom and kitchen. It is applied directly without undercoat and creates excellent results. It has excellent adhesion and high resistance to water, abrasion, soaps, etc.

APPLICATION

Do not apply at temperatures below 6°C or above 40°C or at relative humidity above 80%. It is applied on a well-cleaned surfaces by roller or brush. It is cleaned with a soft cleaner 5 days after finishing the painting. Dissolve with White Spirit at a ratio 1-5%.

VOC (VOLATILE ORGANIC COMPOUNDS)

Product Category A/i (SB) 'One-pack performance coatings' of the EU legislation 2004/42/EU. Maximum limit VOC value of category: 500gr/lt. Maximum VOC concentration of ready to use product 499gr/lt. Product in compliance after 2010 (PhaseII).

Available in White and 3 bases for the coloring system, In metal cans of 750ml & 2.5Lt









RESPONSIBLE DISPOSAL: SAVAS CHALIAMPALIAS & CO Tel. ++30 2310 796663 Fax: ++30 2310 723147 IND. AREA OF THESSALONIKI 57022 SINDOS - GREECE

www.chromodomi.gr



Coverage: 12-14m²/Lt



Drying: 4-5 hours



Dilution: 1-5% White Spirit