

COVER LATEX

HIGH QUALITY EMULSION PAINT

(Version: October 2017 . This issue replace all previous)



PRODUCT DESCRIPTION

High quality emulsion paint for internal use. It provides great coverage, lasting whiteness and high resistant to washing. Exceed Greek (EU) standard's specifications high quality emulsion paint according to the measurements of EL.OT * 7.88.

GENERAL CHARACTERISTICS

COVERAGE	8 - 12m ² /Lt on properly prepared surfaces
DILUTION	First coat 15% water. Second coat 5-10% water
DRYING	1 - 2 hours depending on the conditions
SHADES	White and 3 bases of coloring system
RECOMMENDED UNDERCOATS	Step primer, Life dur water, Step plaster

APPLICATION INSTRUCTIONS

- To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc.
- For new or porous surfaces apply first the recommended undercoat of product
- Stir well the product and apply on 2 coats
- The product has all the mechanical strength after 20-30 days

APPLICATION CONDITIONS

Do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. Adverse conditions in the application can alter the final properties of product.

APPLICATION TOOLS

Brush, Roller, Spray gun

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with warm water and soap. If product dries, clean only with strong detergents. Do not empty washings into the groundwater.

STORAGE

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.

PACKAGING

It is delivered in plastic containers of **750ml, 3Lt, 9Lt**

VOC CLASSIFICATION (VOLATILE ORGANIC COMPOUNDS)

EU limit value for this product (category A/a "Interior matt paints for walls and ceilings" type WB) 30 g/l (2010). This product contains maximum 27 g/l VOC.

WASTE MANAGEMENT

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

HYGIENE & SAFETY INSTRUCTIONS

Keep away from children • Avoid contact with skin and eyes • In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice • If swallowed, seek medical advice immediately • The work area should be well ventilated • When applying recommended to wear gloves and mask protection

CERTIFICATIONS

COVER LATEX is certified by **ELOT 788**, according to laboratory tests which take place in this one.

For more information, consult the MSDS.



chromodomi
paint & insulation

TECHNICAL DATA SHEET

