

## **FAST & RIGHT**

### **SPECIAL ENAMEL PAINT DIRECT TO RUST**

( Version: October 2017 . This issue replace all previous )



#### **PRODUCT DESCRIPTION**

Special enamel that is applied directly on every corroded metal surface, with no need for anticorrosive primers. It is highly adhesive, fast drying finish that provides the easiest and most effective solution against corrosion, giving long term protection on every new or old metal surface.

#### **GENERAL CHARACTERISTICS**

|                               |  |
|-------------------------------|--|
| <b>COVERAGE</b>               | 10 - 12m <sup>2</sup> /Lt on properly prepared surfaces    |
| <b>DILUTION</b>               | 1 - 5% White spirit  |
| <b>DRYING</b>                 | 1 - 2 hours depending on the conditions                    |
| <b>SHADES</b>                 | White, shades of color card and 3 bases of coloring system |
| <b>RECOMMENDED UNDERCOATS</b> | It is applied without undercoat                            |

#### **APPLICATION INSTRUCTIONS**

- To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc.
- Stir well the product and apply direct on corroded surface
- The product has all the mechanical strength after 20-30 days

#### **APPLICATION CONDITIONS**

Do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. Adverse conditions in the application can alter the final properties of product.

## APPLICATION TOOLS

### Brush, Roller

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with White spirit. If product dries, clean only with strong detergents. Do not empty washings into the groundwater.

## STORAGE

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.

## PACKAGING

It is delivered in metallic containers of **750ml, 2.5Lt**

## VOC CLASSIFICATION ( VOLATILE ORGANIC COMPOUNDS )

Product Category A/d (SB) 'Interior/exerior trim and cladding paints for wood and metal' of the EU legislation 2004/42/EU. Maximum limit VOC value of category: 300gr/lit. Maximum VOC concentration of ready to use product 295gr/lit. Product in compliance after 2010 (Phase II)

## WASTE MANAGEMENT

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

## HYGIENE & SAFETY INSTRUCTIONS

Keep away from children • Avoid contact with skin and eyes • In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice • If swallowed, seek medical advice immediately • The work area should be well ventilated • When applying recommended to wear gloves and mask protection

**For more information, consult the MSDS.**

