

FAST & RIGHT METALLIZED

DECORATIVE TEXTURED ENAMEL PAINT

(Version: October 2017 . This issue replace all previous)



PRODUCT DESCRIPTION

Special decorative textured metallized paint. Protects all metal surfaces while offering an excellent aesthetic result. It is applied directly on every corroded metal surface, without using an anticorrosive undercoat. Due to its special composition, provides excellent corrosion protection both new and old rusty surfaces.

GENERAL CHARACTERISTICS

COVERAGE	10 - 12m ² /Lt on properly prepared surfaces
DILUTION	1 - 5% White spirit
DRYING	1 - 2 hours depending on the conditions
SHADES	Silver and shades of color card
RECOMMENDED UNDERCOATS	It is applied without undercoat

APPLICATION INSTRUCTIONS

- To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc.
- Stir well the product and apply one thick coating on surface
- Ensure that all difficult surface points, edges and corners are completely covered, in order to prevent moisture penetration
- The product has all the mechanical strength after 20-30 days

APPLICATION CONDITIONS

Do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. Adverse conditions in the application can alter the final properties of product.

APPLICATION TOOLS

Brush, Roller

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with White spirit. If product dries, clean only with strong detergents. Do not empty washings into the groundwater.

STORAGE

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.

PACKAGING

It is delivered in metallic containers of **750ml, 2.5Lt**

VOC CLASSIFICATION (VOLATILE ORGANIC COMPOUNDS)

Product Category A/d (SB) 'Interior/exerior trim and cladding paints for wood and metal' of the EU legislation 2004/42/EU. Maximum limit VOC value of category: 300gr/lit. Maximum VOC concentration of ready to use product 295gr/lit. Product in compliance after 2010 (Phase II)

WASTE MANAGEMENT

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

HYGIENE & SAFETY INSTRUCTIONS

Keep away from children • Avoid contact with skin and eyes • In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice • If swallowed, seek medical advice immediately • The work area should be well ventilated • When applying recommended to wear gloves and mask protection

For more information, consult the MSDS.

