

## **FLOOR VARNISH**

### **ONE COMPONENT PARQUET VARNISH**

( Version: October 2017 . This issue replace all previous )



#### **PRODUCT DESCRIPTION**

Top quality modified urethane alkyd base, one component glossy varnish for parquets. Suitable for the coating of internal wooden floors. It has got great toughness, gloss, adhesion and resistance to abrasion and scratching. It maintains its high gloss and woods decorative effect for many years.

#### **GENERAL CHARACTERISTICS**

<b>COVERAGE</b>	10 - 15m <sup>2</sup> /Lt on properly prepared surfaces
<b>DILUTION</b>	1 - 5% White spirit
<b>DRYING</b>	2 - 4 hours depending on the conditions
<b>SHADES</b>	Transparent, Satine
<b>RECOMMENDED UNDERCOATS</b>	Wood care

#### **APPLICATION INSTRUCTIONS**

- To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc.
- In old varnished floor, sand with an appropriate abrasive paper to produce a smooth surface
- Apply on surface the recommended undercoat of product
- Stir well the product and apply a coat. After 6 hours apply the second coat
- The product has all the mechanical strength after 20-30 days

#### **APPLICATION CONDITIONS**

Do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. Adverse conditions in the application can alter the final properties of product.

## APPLICATION TOOLS

### Brush, Roller, Spray gun

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with White spirit. If product dries, clean only with strong detergents. Do not empty washings into the groundwater.

## STORAGE

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.

## PACKAGING

It is delivered in metallic containers of **750ml, 3Lt**

## VOC CLASSIFICATION ( VOLATILE ORGANIC COMPOUNDS )

Product Category A/f (SB) 'Interior/exterior minimal built woodstains' of the EU legislation 2004/42/EU. Maximum limit VOC value of category: 700gr/lit. Maximum VOC concentration of ready to use product 695gr/lit. Product in compliance after 2010 (Phase II).

## WASTE MANAGEMENT

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

## HYGIENE & SAFETY INSTRUCTIONS

Keep away from children • Avoid contact with skin and eyes • In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice • If swallowed, seek medical advice immediately • The work area should be well ventilated • When applying recommended to wear gloves and mask protection

**For more information, consult the MSDS.**



SAVAS CHALIAMPALIAS & CO

INDUSTRIAL AREA OF THESSALONIKI, 57 022 SINDOS, GREECE - TEL. ++30 2310.79.79.72 – FAX: ++30 2310 723.147

**www.chromodomi.gr**