

## **LIFE DUR SILICON WATER**

### **SILICON WATER BASED PRIMER**

( Version: October 2017 . This issue replace all previous )



#### **PRODUCT DESCRIPTION**

Transparent silicon water based primer for walls with great adhesion and high penetration for internal and external use. It is the most suitable material for priming of surfaces that are to be painted with silicon based acrylic or emulsion paints. It allows the wall to “breathe” taking out the moisture, but prohibiting it to penetrate. It must be used only on new surfaces, or on those that are painted with silicon based paint, because it loses the property of breathing, if it is applied on traditional paints.

#### **GENERAL CHARACTERISTICS**

<b>COVERAGE</b>	15 - 20m <sup>2</sup> /Lt on properly prepared surfaces
<b>DILUTION</b>	50 - 100% water
<b>DRYING</b>	1 - 2 hours depending on the conditions
<b>SHADES</b>	Transparent

#### **APPLICATION INSTRUCTIONS**

- To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc.
- Apply the product with brush or roll and let it dry for 1 - 2 hours.
- Apply the top coat.
- The product has all the mechanical strength after 20-30 days

#### **APPLICATION CONDITIONS**

Do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. Adverse conditions in the application can alter the final properties of product.

