

LIFE DUR

WATERPROOF UNDERCOAT FOR WALLS & ROOFS

(Version: October 2017 . This issue replace all previous)



PRODUCT DESCRIPTION

Special waterproof undercoat with good bonding and penetration suitable for internal and external surfaces. It provides a ready surface for repainting with emulsion or acrylic paints, as well as for waterproofing coatings for vertical or horizontal surfaces. It dries very fast, it is durable at yellowing. Ideal for walls & roofs.

GENERAL CHARACTERISTICS

| | |
|-----------------|---|
| COVERAGE | 10 - 12m ² /Lt on properly prepared surfaces |
| DILUTION | 100% White spirit for vertical surfaces 80% White spirit for horizontal surfaces |
| DRYING | 1 - 2 hours depending on the conditions |
| SHADES | Transparent |

APPLICATION INSTRUCTIONS

- To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc.
- Apply the product with brush or roll and let it dry for 1 - 2 hours.
- Apply the top coat.
- The product has all the mechanical strength after 20-30 days

APPLICATION CONDITIONS

Do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. Adverse conditions in the application can alter the final properties of product.

APPLICATION TOOLS

Brush, Roller

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with White spirit. If product dries, clean only with strong detergents. Do not empty washings into the groundwater.

STORAGE

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.

PACKAGING

It is delivered in metallic containers of **750ml, 5Lt, 16Lt**

VOC CLASSIFICATION (VOLATILE ORGANIC COMPOUNDS)

Product Category A/h (SB) 'Binding Primers' of the EU legislation 2004/42/EU. Maximum limit VOC value of category: 750gr/lit. Maximum VOC concentration of ready to use product 745gr/lit. Product in compliance after 2010 (Phase II).

WASTE MANAGEMENT

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

HYGIENE & SAFETY INSTRUCTIONS

Keep away from children • Avoid contact with skin and eyes • In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice • If swallowed, seek medical advice immediately • The work area should be well ventilated • When applying recommended to wear gloves and mask protection

For more information, consult the MSDS.

