

MOTOR LAC

FAST DRYING SYNTHETIC ENAMEL PAINT

(Version: October 2017 . This issue replace all previous)



PRODUCT DESCRIPTION

Fast drying, excellent quality synthetic enamel paint. It has excellent durability, long lasting gloss, withstands in hits, and has high resistance in the most adverse weather conditions. Suitable for all metal surfaces such as machinery, heavy vehicles and metal constructions.

GENERAL CHARACTERISTICS

COVERAGE	12 - 15m ² /Lt on properly prepared surfaces
DILUTION	1 - 5% Nitro thinner or White spirit
DRYING	20 - 40 min depending on the conditions
SHADES	White, 23 RAL shades and 3 bases of coloring system
RECOMMENDED UNDERCOATS	Primer, Chassis coat, Velatura

APPLICATION INSTRUCTIONS

- To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc.
- Apply on surface the recommended undercoat of product
- Stir well the product and apply on surface
- The product has all the mechanical strength after 20-30 days

APPLICATION CONDITIONS

Do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. Adverse conditions in the application can alter the final properties of product.

APPLICATION TOOLS

Brush, Roller

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with White spirit. If product dries, clean only with strong detergents. Do not empty washings into the groundwater.

STORAGE

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.

PACKAGING

It is delivered in metallic containers of **750ml, 2.5Lt**

VOC CLASSIFICATION (VOLATILE ORGANIC COMPOUNDS)

Product Category B/d (SB) 'Topcoat-All types' of the EU legislation 2004/42/EU. Maximum limit VOC value of category: 420gr/lit. Maximum VOC concentration of ready to use product 419gr/lit. Product in compliance after 2007.

WASTE MANAGEMENT

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

HYGIENE & SAFETY INSTRUCTIONS

Keep away from children • Avoid contact with skin and eyes • In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice • If swallowed, seek medical advice immediately • The work area should be well ventilated • When applying recommended to wear gloves and mask protection

For more information, consult the MSDS.



SAVAS CHALIAMPALIAS & CO

INDUSTRIAL AREA OF THESSALONIKI, 57 022 SINDOS, GREECE - TEL. ++30 2310.79.79.72 – FAX: ++30 2310 723.147

www.chromodomi.gr