

STEP PRIMER

ACRYLIC EMULSION UNDERCOAT

(Version: October 2017 . This issue replace all previous)



PRODUCT DESCRIPTION

Ideal whitish undercoat that prepares every surface for painting. It has great adhesion and it “bonds” the surfaces to be painted. Ideal for plasterboards, plaster etc. It intensifies the adhesion of emulsion paints and it reduces their consumption. As it is acrylic, it can be used without a problem on external walls, too. Its application is necessary for the “turning” of the coating from hydrochroma to emulsion paint.

GENERAL CHARACTERISTICS

COVERAGE	20 - 25m ² /Lt on properly prepared surfaces
DILUTION	300% water
DRYING	1 - 2 hours depending on the conditions
SHADES	Whitish and colored

APPLICATION INSTRUCTIONS

- To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc.
- Apply the product with brush or roll and let it dry for 1 - 2 hours.
- Apply the top coat.
- The product has all the mechanical strength after 20-30 days

APPLICATION CONDITIONS

Do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. Adverse conditions in the application can alter the final properties of product.

APPLICATION TOOLS

Brush, Roller

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with warm water and soap. If product dries, clean only with strong detergents. Do not empty washings into the groundwater.

STORAGE

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.

PACKAGING

It is delivered in metallic containers of **750ml, 3Lt, 10Lt**

VOC CLASSIFICATION (VOLATILE ORGANIC COMPOUNDS)

EU limit value for this product (Category A/g "Primers" Type WB) is 30 g/l (2010). This product contains maximum 27 g/l VOC.

WASTE MANAGEMENT

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

HYGIENE & SAFETY INSTRUCTIONS

Keep away from children • Avoid contact with skin and eyes • In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice • If swallowed, seek medical advice immediately • The work area should be well ventilated • When applying recommended to wear gloves and mask protection

For more information, consult the MSDS.

