

TEAK OIL

WATER-BASED OIL FOR WOOD

(Version: October 2017 . This issue replace all previous)



PRODUCT DESCRIPTION

Colourless teak oil for internal and external use at hard wood. Special elaboration with filters UV that protects and maintains exterior furniture, teak desks or exotic wood. It feeds and protects from water, sun, saltiness and greasy substances. It leaves the wood to breathe electing his natural beauty. When it dries out it does not smudge.

GENERAL CHARACTERISTICS

COVERAGE	10 - 15m ² /Lt on properly prepared surfaces
DILUTION	Ready to use
DRYING	Touch dry after 2-3 hours. Recoatable after 2 days
SHADES	Transparent

APPLICATION INSTRUCTIONS

- To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc.
- Sand with an appropriate abrasive paper the surfaces that have been passed with other Teak oil materials, so that the wood pores open and the material can imbue in the surface.
- Apply a coat of the product with a soft cloth or with brush
- For surfaces exposed to extreme weather conditions, apply after 2 days the second coat
- The product has all the mechanical strength after 20-30 days

APPLICATION CONDITIONS

Do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. Adverse conditions in the application can alter the final properties of product.

APPLICATION TOOLS

Brush, Soft cloth

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with warm water and soap. If product dries, clean only with strong detergents. Do not empty washings into the groundwater.

STORAGE

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.

PACKAGING

It is delivered in metallic containers of **750ml, 3Lt**

VOC CLASSIFICATION (VOLATILE ORGANIC COMPOUNDS)

Product category A/f (WB) "Minimal build woodstains" of 2004/42/EC. Maximum limit VOC value of category: 130gr/lit. Maximum VOC concentration of ready to use product: 127gr/lit. Product in compliance after 2010 (Phase II).

WASTE MANAGEMENT

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

HYGIENE & SAFETY INSTRUCTIONS

Keep away from children • Avoid contact with skin and eyes • In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice • If swallowed, seek medical advice immediately • The work area should be well ventilated • When applying recommended to wear gloves and mask protection

For more information, consult the MSDS.

