

## **UNMOULD HYDROCHROMA**

### EXTRA WHITE PAINT FOR INTERNAL CEILINGS

( Version: October 2017 . This issue replace all previous )



#### PRODUCT DESCRIPTION

Extra white paint for internal use. It has got great resistance in the fungi of moisture and in the dry abrasion and covers all the surfaces with 2 coats. It is suggested for use in baths, kitchens and generally in every place that favors the growth of fungi and mold.

#### GENERAL CHARACTERISTICS

<b>COVERAGE</b>	4 - 6m <sup>2</sup> /Lt on properly prepared surfaces
<b>DILUTION</b>	First coat 15% water. Second coat 5-10% water
<b>DRYING</b>	1 - 2 hours depending on the conditions
<b>SHADES</b>	White
<b>RECOMMENDED UNDERCOATS</b>	Step primer, Life dur water

#### APPLICATION INSTRUCTIONS

- To ensure proper adhesion of the product, surfaces must be clean, dry and free from all defective and poorly adhering material, dust, grease, oil, rust, mold or moisture etc.
- For new or porous surfaces apply first the recommended undercoat of product
- Stir well the product and apply on 2 coats
- The product has all the mechanical strength after 20-30 days

#### APPLICATION CONDITIONS

Do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. Adverse conditions in the application can alter the final properties of product.

## APPLICATION TOOLS

### Brush, Roller, Spray gun

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with warm water and soap. If product dries, clean only with strong detergents. Do not empty washings into the groundwater.

## STORAGE

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.

## PACKAGING

It is delivered in plastic containers of **3Lt, 9Lt**

## VOC CLASSIFICATION ( VOLATILE ORGANIC COMPOUNDS )

EU limit value for this product (category A/a "Interior matt paints for walls and ceilings "type WB) 30 g/l (2010). This product contains maximum 27 g/l VOC.

## WASTE MANAGEMENT

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

## HYGIENE & SAFETY INSTRUCTIONS

Keep away from children • Avoid contact with skin and eyes • In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice • If swallowed, seek medical advice immediately • The work area should be well ventilated • When applying recommended to wear gloves and mask protection

**For more information, consult the MSDS.**

