

# Stamped floors varnish

acrylic varnish for stamped concrete floors

## PRODUCT DESCRIPTION

One component acrylic varnish for stamped concrete floors, suitable for decoration and protection of interior and exterior surfaces. It has strong adhesion, elasticity and resistance to weather conditions. Dries in 30 minutes, recoated after 2-3 hours. Full cure after 24 hours.



## TECHNICAL CHARACTERISTICS

<b>Specific gravity</b>	0,87	gr/cm <sup>3</sup> (23°C)	ISO EN2811.01 - 2011
<b>Viscosity</b>	200 - 500	mPas (23°C)	ISO EN 2555 - 1999
<b>Solids content by weight</b>	12 - 14	%	ISO EN 3251 - 2008
<b>Solids content by volume</b>	14 - 16	%	ISO EN 3233 - 1998

## GENERAL CHARACTERISTICS

<b>Coverage</b>	10m <sup>2</sup> /Lt on properly prepared surfaces
<b>Dilution</b>	Ready to use
<b>Drying</b>	30 min depending on conditions. Full cure after 24 hours.
<b>Shades</b>	Clear

## APPLICATION INSTRUCTIONS

It is applied on a well-cleaned surfaces by roller or brush at 2 coats.

## APPLICATION CONDITIONS

Do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. Adverse conditions in the application can alter the final properties of product.

## APPLICATIONS TOOLS

### Brush, roller

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with White spirit. If product dries only with strong detergents. Do not empty washings into the groundwater.



## STORAGE

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.

## PACKAGING

It is delivered in metallic containers of **5Lt, 20Lt**

## VOC CLASSIFICATION (VOLATILE ORGANIC COMPOUND)

Product Category A/h (SB) 'Binding Primers' of the EU legislation 2004/42/EU. Maximum limit VOC value of category: 750gr/lit. Maximum VOC concentration of ready to use product 745gr/lit.

Product in compliance after 2010 (Phase II)

## WASTE MANAGEMENT

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

## HYGIENE & SAFETY INSTRUCTIONS

### HAZARDS STATEMENTS:

**H226:** Flammable liquid and vapour • **H315:** Causes skin irritation • **H312:** Harmful in contact with skin • **H332:** Harmful if inhaled • **H372:** Causes damage to organs through prolonged or repeated exposure • **H412:** Harmful to aquatic life with long lasting effects.

### PRECAUTIONARY STATEMENTS:

**P210:** Keep away from heat/sparks/open flames/hot surfaces. - No smoking • **P260:** Do not breathe dust/fume/gas/mist/vapours/spray • **P271:** Use only outdoors or in a well-ventilated area • **P280:** Wear protective gloves/protective clothing/eye protection/face protection • **P302+P352:** IF ON SKIN: Wash with plenty of soap and water • **P332+P313:** If skin irritation or rash occurs: Get medical advice/attention • **P264:** Wash hands thoroughly after handling • **P501:** Dispose of contents/container according to local and national regulations. **CONTAINS:** Hydrocarbons C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), Xylene.



**DANGER**

For more information, consult the MSDS.



The company is certified to standards  
EN ISO 9001:2008 / EN ISO 14001:2004

Version: July 2016  
This issue replaces all previous